



## Home/Commercial Booster Boost 4G LTE F15G-5S

### Overview

Boost 4G LTE (F15G-5S) is a 65dB, ultra wide band cell phone signal booster that covers up to 5,000 square feet with clear voice and high speed 2G, 3G and 4G data. It can also support large capacities of 100 cell phones users. With our Boost 4G LTE, enjoy clear calls and high speed data all around your house at the lowest price guaranteed.



### FCC fulfillment

- FCC Grant Code OWW for this series product. To get detail information, go to <https://apps.fcc.gov/oetcf/eas/reports/GenericSearch.cfm>
- FCC approved this equipment for use with all US carriers
- The FCC ID for this equipment is OWWF15G-CPAL-AB-C



### Key Features

- All 2G, 3G and 4G standards are supported
- Supported up to 100 users
- Does not require professional installation
- Low interference to cell tower
- FCC certified
- MGC function special for electric fans
- Streamline design
- Quality metal construction, strong and durable



### Booster Kit Includes

- Boost 4G LTE 65dB cell phone booster
- Outdoor Logarithmic periodic antenna with 30 feet 3D-FB cable
- Indoor panel antenna with 15 feet 3D-FB cable

---

Address: 6210 N. Belt Line Road, Suite 110, Irving, TX 75063 Phone: (972)870-5666 E-mail: [info@huaptecus.com](mailto:info@huaptecus.com)  
Website: [www.huaptecus.com](http://www.huaptecus.com)

---



Designed and Produced By Huaptec

## Specification

Electrical specification	
UL Frequency Range	698-716 / 776 – 787 / 824-849 / 1850-1910 / 1710-1755
DL Frequency Range	728-746 / 746 – 757 / 869-894 / 1930-1990 / 2110-2155
Supported Standards	CDMA, WCDMA, GSM, EDGE, HSPA+, EVDO, LTE and all cellular standards
Max .Gain	65dB
MGC ( Step Attenuation )	31dB/1dB step
Automatic Gain Control	31dB
I/O Port	N-Female
Impedance	50 ohm
Environment Conditions	IP40
Dimensions	8.6*6.5*2inch/218*165*50mm
Weight	≤5.5Lbs/2.5Kg
Power Supply	Input AC100~240V,50/60Hz,Output DC12V / 3A

## Installation Example

