

CENTURION™ 9-in-1

High Performance External Antenna with Hex Wi-Fi

CENTURION 9-in-1 is a full outdoor antenna equipped with 9 ports available pre-configured to connect directly to **Cradlepoint's IBR1700 or Sierra Wireless MG90** router, designed specifically to provide high performance connectivity for Fleet and Public Safety vehicles and assets connecting to almost any vehicular router or modem. This antenna is configurable and offers up to two high gain cellular/LTE/ MIMO antennas, which include support for LTE Band 14 for FirstNet, 6 high gain Wi-Fi antennas, and a GNSS antenna inside a single robust and compact housing. This antenna provides the ultimate in Wi-Fi support - with integrated 6x6 Wi-Fi antennas, providing support for full HD streaming video and other high bandwidth applications.

- 2 x Wideband Cellular/LTE Elements (MIMO)
- 6 x 2.4 & 4.9-6GHz Wi-Fi Elements (MIMO)
- 1 x GNSS Element
- Nine embedded antenna technologies that operate over multiple bands in one housing
- Leading LTE performance while in coexistence with multiple other embedded antenna technologies
- Lower profile and smaller footprint than competing solutions
- High gain provides bigger cellular footprint
- Must be mounted on metal
- Available in black or white
- US Patent 10109918

Descriptions/Applications

The CENTURION 9-in-1 antenna builds on the best in class RF performance, leading design features, and extended operational life of our highly successful Fleet and Public Safety Antenna products. Like all our antennas, this product has been designed to be robust to withstand the natural hazards a vehicle faces including vibration, hot, cold, ice, salt, dirt, car washes, and tree branch sweeps. Our antennas typically outlast the life of a vehicle.

Standard Configurations

AP-C2W6G-Q-SMA-RP345678-BL-15	MIMO Cell/LTE x 2, Wi-Fi x 6 & GNSS, Threaded Bolt Mount, SMA on Cell/LTE & GNSS, RP-SMA on Wi-Fi, Black, 15ft coax
AP-C2W6G-A-SMA-RP345678-BL-15	MIMO Cell/LTE x 2, Wi-Fi x 6 & GNSS, Adhesive Mount, SMA on Cell/LTE & GNSS, RP-SMA on Wi-Fi, Black, 15ft coax
AP-C2W6G-M-SMA-RP345678-BL-15	MIMO Cell/LTE x 2, Wi-Fi x 6 & GNSS, Magnetic Mount, SMA on Cell/LTE & GNSS, RP-SMA on Wi-Fi, Black, 15ft coax

Also available in color white, customizable cable lengths up to 35 feet, and other connector variations.



Optimal MIMO Performance for LTE



Compact and Robust UV Resistant Housing



Full Outdoor Installation Ready



Customizable Cables and Connectors to Connect to Any Modem



Flexible Mounting Options



GNSS



Low loss cable accessories



Fast custom turnaround time



Bolt Mount



Adhesive Mount



Magnetic Mount

Electrical Data

Frequency Range	Elements 1 & 2	698-960/1700-2700 MHz	
	Elements 3, 4, 5, 6, 7, & 8	2.4/4.9-6.0 GHz	
	Element 9	1550~1610 MHz	
Operational Bands	Elements 1 & 2	LTE/Cellular	
	Elements 3, 4, 5, 6, 7, & 8	Wi-Fi	
	Element 9	GPS L1/GALILEO E1/GLONASS G1/BeiDou B1	
Peak Gain: Isotropic	Elements 1 & 2	698-960 MHz	4 dBi
		1710-2700 MHz	7 dBi
	Elements 3, 4, 5, 6, 7, & 8	2.4 GHz, 5.5 GHz	7 dBi, 4 dBi
	Element 9	30.50 dBi	
Isolation	Elements 1 & 2	> 10 dB	
	Elements 3, 4, 5, 6, 7, & 8	> 30 dB	
Correlation Co-efficient	Elements 1 & 2	< 0.1	

Environmental Data

Hazardous Substances	RoHS Compliant
Temperature	-40 °C to 85 °C (-40 °F to + 185 °F) Operating and Storage
Humidity (Non-Condensing)	-5% to 95% Operating and Storage
Military Spec	MIL-STD 810 conformance to vibration and humidity

Mounting Data

Dimensions	Height	2.220" (56.4mm)
	Width	3.831" (97.3mm)
	Length	7.000" (117.8mm)
Operating Temp	-22°/176°F(-30°/+80°C)	
Color	Black (BL) or White (WH)	

Cable Data

Cell/LTE & GNSS	Type	CFD195 Low Loss	Wi-Fi	CFD195 Low Loss
	Diameter	0.195" (4.953 mm)		0.195" (4.953 mm)
	Length	1 feet (0.3 m)		1 feet (0.3 m)
	Termination	SMA Male		RP-SMA Male

GNSS Data - Ceramic Patch Antenna Specification

Bandwidth	1561 – 1602 MHz
Gain@Zenith	2.5 dBi
Polarization	R.H.C.P.
Axial Ratio	3.0 dB Typ.

GNSS Data - LNA Specification

Noise Figure	1.2 dB
Gain	28 dBi
Voltage	3.3V~5.6V
Current	9.6±1mA@3.3V