



3-Cable
Multiband

Surface Mount Multiband PTC 220 MHz, WiFi & GPS

- 3 antennas in 1 antenna housing
- Designed for Positive Train Control (PTC) at 220 MHz along with WiFi and GPS
- Rugged, heavy duty construction

The SMW-PTC Series Antenna was designed for PTC (Positive Train Control) applications. Designed & built with heavy duty construction to survive the rigors of railroad use.

This antenna uses our popular SMW Series platform to combine PTC with WiFi and GPS. As with our other SMW antennas, this antenna contains 3-elements all within the same radome. The first element covers 220-220 MHz, the second element covers 2.4-2.5 GHz and the third covers GPS at 1575 MHz.

The SMW-PTC antennas provide 2 dBi gain on the PTC element, 5 dBi gain on the WiFi element, and 5 dBi gain with a 26 dB amplifier on the GPS element. The antennas will handle 10 watts of power.

The surface mount models use a 3/4-inch feed thru (19 mm) for securing to the vehicle. Access to the underside of the body surface is required to complete the installation of the SMW Series. For best performance the antenna should be mounted on a metal surface or ground plane. A mag-mount option is not available.

The antenna is enclosed in a 4.2"D x 3.2"H (107 mm x 81 mm) weatherproof radome, and supplied with all mounting hardware and a sealing gasket. The radome is available in either black or white.

Model Configurator

SMW-PTC-1 - -

Connector 1

Cable/Connector 2

Cable/Connector 3

Color

Cable Length in Inches (eg. 12 or 180)

Example: SMW-PTC-1C3C2C-WHT-180

Specify "SMWG" instead of "SMW"
for GPS/Glonass combination antenna.

Cable Options:		Connector Options:		Color Options:	
Code	Cable	Code	Connector	Code	Color
1	RG-58	A	TNC	WHT	White
2	RG-174	B	Mini UHF	BLK	Black
3	LL-195	C	SMA		
		D	SMB		
		E	MCX		

(Other Configurations available.)

Specifications			
Frequency & Gain (peak):	Cable 1 Cable 2 Cable 3 (GPS)	220-222 MHz, 2 dBi 2400-2485 MHz, 5 dBi 1575.42 +/- 2 MHz, LNA 26dB 5 dBi nominal RHCP, Antenna	Cable: Cable 1 (220) Cable 2 (WiFi) Cable 3 (GPS) Connectors:
VSWR:	2:1 max over range	Nominal Impedance:	50 ohms
Power:	10 Watts	Mounting:	Threaded metal stud 3/4" dia. x 1/2" long (19 mm x 13 mm) for 1/4" (6 mm) thick metal; supplied with gasket and nut
GPS:	Noise Figure Amplifier Bias Amplifier Current	2.0 dB max, 1.7 dB typical 2.7 to 5 VDC 20 mA, 10 mA typical	Operating Temp: Shock & Vibration:
GPS & Glonass Option:	1575 MHz & 1612 MHz	Case: Case Material:	-40° to +80° C IEEE1478, EN 61373, MIL-810G, TIA 329.2-C IP67
Case:	4.2"D x 3.2"H (107 mm x 81 mm)	Dust/Water Ingress:	IP67
Case Material:	White or Black UV resistant ASA		