




Directional Yagi with Standard wall mounting



Optional Swivel pipe mounting

Directional Yagi Antennas High frequency 4.4-6.0 GHz

- Slim attractive profile, 7.5" total length including mounting bracket
- High gain for efficient point-to-point
- Can be used for DAS & In-building applications or mounted outside

This high quality and reliable Yagi Antenna can be used for any of the wireless applications that fall in the 4.4-6.0 GHz frequency range. These include WiFi 5 GHz, DSRC 5.9 GHz, Public Safety 4.9 GHz or Military 4.4 GHz.

The YAG12 antenna's compact size also makes it a nature choice for In-building installations.

The YAG12 Series offers 10 dBi gain from 4.4-5.4 GHz and 12 dBi gain from 5.47-6.0 GHz. This makes the antenna very effective for applications such as mesh systems, point-to-point or point-to-multi-point.

ISP and Service Providers will find these antennas particularly efficient for short range backhaul applications or for providing coverage in hard to cover areas such as in an in-building corridor.

The antenna's compact profile and White color helps this Yagi fit in anywhere. The antenna measures only 6.35" long x 2.75" high x .56" wide (16 cm x 7 cm x 1.3 cm).

The slim profile makes this antenna aesthetically pleasing for indoor use.

The radome is made from ASA, which resists discoloration by UV rays even if the product is exposed to many years of sunlight.

Mounting options for this antenna include both wall mounting and optional pipe mounting. The unique adjustable mount has a 45° adjustable range both in the vertical range and the horizontal range.

Cable assemblies are available including low loss-195, RG-58, LMR-240 and LMR-400. Choices of connectors include SMA, TNC, and N connectors.

Model #	Gain	Connector
YAG12-5500-3C-WHT-12	10 & 12 dBi	SMA Plug
YAG12-5500-3X-WHT-12	10 & 12 dBi	N Plug
YAG-PMK	Optional pipe mount	
For cable jumpers & other connectors, please contact your sales representative		

Specifications			
Frequency & Gain:	4.4-5.4 GHz, 10 dBi 5.47-6.0 GHz, 12 dBi	Adjustment:	Both vertical and horizontal adjustment up to 45°
VSWR:	2:1 max over range	Radome Size:	2.75" H x 6.35" L x 0.56" W (7 cm x 16 cm x 1.4 cm)
Impedance:	50 Ohm nominal	Size with mount:	2.75" x 7.5" x .56" (7 cm x 19 cm x 1.4 cm)
Maximum Power:	25 Watts	Cable:	1 ft (30.5 cm) low loss-195
Beamwidth:	30° elevation, 55° azimuth	Termination:	SMA Plug or N Plug, others available
Front-to-Back ratio:	Better than 15 dB	Shock & Vibration	EN 300 019-2-4, IEC 60068
Operating Temp:	-40°C to +85°C	Water Ingress:	IPx5
Lightning Protection:	External recommended		
Antenna Radome:	ASA, White		
Weight:	.5 lbs (0.23 kg)		
Mounting:			
Standard	45° adjustable Swivel Wall Mnt.		
Optional	45° adjustable Swivel Pipe Mnt.		